

	K 2413F	K 2415
AC Current Range and Accuracy	200mA $\pm(1.5\% + 2 \text{ dgt})$ at 50/60Hz 2A 20A $\pm(3.0\% + 2 \text{ dgt})$ at 40Hz - 1kHz 200A $\pm(2.0\% + 2 \text{ dgt})$ at 50/60Hz 1000A $\pm(3.5\% + 2 \text{ dgt})$ at 40Hz - 1kHz (for currents less than 500A)	20mA $\pm(1.5\% + 2 \text{ dgt})$ at 50/60Hz 2A $\pm(2.0\% + 5 \text{ dgt})$ at 40Hz - 1kHz 100A $\pm(2.0\% + 5 \text{ dgt})$ at 50/60Hz $\pm(2.5\% + 5 \text{ dgt})$ at 60Hz - 1kHz
AC Voltage Range and Accuracy	-	500V $\pm(1.5\% + 2 \text{ dgt})$ at 50/60Hz $\pm(2.0\% + 5 \text{ dgt})$ at 40Hz - 1kHz
Output Voltage Range and Accuracy	0 - 400A, 0 - 2A, 0 - 20A, 0 -200A 0 - 500A 0 - 500A 500A-1000A	0 - 200mV AC or DC 0 - 50mV AC or DC 50 - 100mV AC or DC
Frequency	50/60Hz, 40Hz - 1kHz (user selectable)	50/60Hz, 40Hz - 1kHz (user selectable)
Withstand Voltage	3000V AC for 1 minute	2200V AC for 1 minute
Dimensions	250 x 130 x 50mm	173 x 80 x 36mm
Weight	570g	210g
Power Source	1 x 9V PP3	2 x 1.5V AA