

| FEATURES | 5XP-A | 15XP-A | 35XP-A |
|----------------------------|--|---|---|
| DC Voltage | 200.0mV, 2.000, 20.00, 200.0, 1000V | | 400.0m, 4.000, 40.00, 400.0, 1000V |
| AC Voltage | 200.0mV, 2.000, 20.00, 200.0, 750V | | 400.0m, 4.000, 40.00, 400.0, 750V |
| Current AC/DC | 200.0μ, 2.000m, 20.00m, 200.0mA | 200.0μ, 2.000m, 20.00m, 200.0m, 2A | 400.0μA, 4.000μA, 40.00mA, 400.0mA, 2A |
| Resistance | 200.0 Ω, 2.000k, 20.00k, 200.0k, 2.000M, 20.00MΩ | 200.0 Ω, 2.000k, 20.00k, 200.0k, 2.000M, 20.00M, 2000MΩ | 400.0, 4.000k, 40.00k, 400.0k, 4.000M, 40.00MΩ |
| Continuity beeper | Yes | | |
| Non-contact voltage | 70 V to 600 VAC (50 Hz to 60 Hz) | | |
| Capacitance | N/A | | 4.000n, 40.00n, 400.0n, 4.000μ, 40.00μ, 400.0μ, 4.000mF |
| Frequency | N/A | | 4.000k, 40.00k, 400.0k, 1MHz |
| Temperature | N/A | | -20 °C to 1000 °C |
| Logic test | N/A | TTL, 20 MHz | N/A |
| Battery test | 1.5 V, 9 V | N/A | |

Available on all XP Series meters: Magne-Grip™ Holster with magnetic hanging strap frees both hands for work. VolTect™ non-contact voltage detection lets you instantly detect dangerous ac line voltages.